

Standard System includes:

- Fitted Carrying Case
- User Manual



The HI-1600 Microwave Meter accurately measures microwave leakage at both 915MHz and 2450MHz.

Three survey ranges are incorporated into a switching sequence that includes positions for battery and probe checks.

Specifications:

Frequency Response Ranges	915 MHz & 2450 MHz 0-10 mW/cm ² at 2450MHz 0-10, 0-20 mW/cm ² at 915MHz
Accuracy	± 1 dB
Response Time	Fast Mode: 1sec Slow Mode: 2.5 secs
	(to 90% of Impulse Level)
Maximum Power Density	2 W/cm ²
Dimensions (3.5" x 6" x 2.5")	8.9 W x 15.3 H x 6.4 D cm
Probe Length	30cm (12")
Probe Cable Length	1.2m (4')

USA

Tel +1.512.531.6400
Fax +1.512.531.6500

Finland

Tel +358.2.8383.300
Fax +358.2.8651.233

UK

Tel +44.1438.730.700
Fax +44.1438.730.751

France

Tel +33.1.48.65.34.03
Fax +33.1.48.65.43.69

China

Tel +8610.8275.5086
Fax +8610.8275.5537

Japan

Tel +81.3.3813.7100
Fax +81.3.3813.8068