

# PROVA

## Anemometer

### MODEL AVM-01/AVM-03

- Sensitive for low/high air velocity
- Ergonomic Design
- 0.3~45m/s range



### Specification for AVM-01/AVM-03 (23.0 +/- 5oC)

	Measurement	Range	Resolution	Accuracy
Air Velocity	M/S	0.3-45.0	0.1	+/- 3% or 0.1
	KNOTS	0.6-88.0	0.1	+/- 3% or 0.1
	ft/min	60-8800	10	+/- 3% or 10
	Km/hr	1-140.0	0.1	+/- 3% or 0.1
Optional Range	MPH	0.7-100.0	0.1	+/- 3% or 0.1
Temperature AVM-03	°C	0-60	0.1	+/- 0.8
Temperature AVM-03	°F	32-140	0.1	+/- 1.5

**Operating Temperature:** 10oC-50oC

**Operating Pressure:** 500mB-2bar

**Display:** Large 3 1/2 digit LCD

**Power Source:** 1pc of 9V Battery

**Dimension:** 168mm x 90mm x 31.3mm

**Weight:** 500g

**Accessory:** Carrying Case, 9V Battery, Instruction Manual

Distribuye



**Vimelec S.A.**

Virrey Liniers 1882 (C1241ABN) Buenos Aires  
Tel/Fax: (54 11) 4912-3998 / 4204 ó (54 11) 4911-7304  
E-mail: vimelec@vimelec.com.ar  
Sitio web: www.vimelec.com.ar