

PROVA

AC/DC mA Current Probe

MODEL PROVA 15

- High Resolution DC 1mA, AC 0.1mA
- Connect to an Oscilloscopes to observe Current Waveform
- Connect to Chart Recorder/Datalogger/DMM to Record Current Data



Specifications for PROVA 15

Range	Output	Sensitivity	Accuracy
DCA 0-400mA	DC 1mV/A	1mA/mV DC	+/- 2.0% +/- 1mV
DCA 0-4A	DC 100mV/A	10mA/mV DC	+/- 1.0% +/- 0.5mV
DCA 0-30A	DC 10mV/A	0.1A/mV DC	+/- 1.0% +/- 0.3mV
ACA 0-400mA	AC 1mV/A	1mA/mV AC	+/- 2.0% +/- 0.5mV
ACA 0-4A	AC 100mV/A	10mA/mV AC	+/- 1.5% +/- 0.8mV
ACA 0-30A	AC 10mV/A	0.1A/mV AC	+/- 1.5% +/- 0.3mV

Power Source: 2 X 1.5V AA UM3 Batteries

Current Consumption: 10mA

Operating Condition: -10°C to 50°C at 85% max. RH

Distribuye

 **Vimelec S.A.**

Virrey Liniers 1882 (C1241ABN) Buenos Aires
Tel/Fax: (54 11) 4912-3998 / 4204 ó (54 11) 4911-7304
E-mail: vimelec@vimelec.com.ar
Sitio web: www.vimelec.com.ar