



DIGITAL TACHOMETER

MODEL RM-1500/RM-1501

- 5 Digits LCD Display
- Range 10.0~99,999RPM
- Measuring Distance 50~300mm
- Combination type for non-contact and contact measurements
- Counter (0~99999)
- RS-232 (RM-1501)



Specifications for RM-1500/RM-1501 (23°C±5°C)

RPM (non-contact measuring , Autorange):

Range	Resolution	Accuracy
10.0~6,000.0rpm	0.1rpm	+/-0.01%±1digit
6,000.0~9,999.9rpm	0.1rpm	+/-0.02%±1digit
1,0000~12,000rpm	1rpm	+/-0.02%±1digit
12,000~30,000rpm	1rpm	+/-0.05%±1digit
Over 30,000rpm	1rpm	+/-0.1%±1digit

RPM (contact measuring , Autorange):

Range	Resolution	Accuracy
10.0~6,000.0rpm	0.1rpm	+/-0.01%±1digit
6,000.0~9,999.9rpm	0.1rpm	+/-0.02%±1digit
1,0000~12,000rpm	1rpm	+/-0.02%±1digit
12,000~30,000rpm	1rpm	+/-0.05%±1digit
Over 30,000rpm	1rpm	+/-0.1%±1digit

General Specification:

Battery: Four 1.5V battery (AA, UM3)

Time Base: 4.000MHz Quartz Crystal

Operating Temperature: 0°C~ 50°C (32°F~122°F)

Reflective light: Red LED

Size: 6.8"(L) x 2.5"(W) x 1.4"(H)
175mm(L) x 65mm(W) x 36mm(H)

Weight: 250g (including battery)

Accessories: Carrying Case x 1
Reflective tape x 1
Instruction Manual x 1

Option: Contact Adaptor

Distribuye



Vimelec S.A.
Virrey Liniers 1882 (C1241ABN) Buenos Aires
Tel/Fax: (54 11) 4912-3998 / 4204 ó (54 11) 4911-7304
E-mail: vimelec@vimelec.com.ar
Sitio web: www.vimelec.com.ar