

# DIGITAL MULTIMETER

**NEW**

**KEW1011** with "K" type Temperature probe

**KEW1012** with True RMS



**KEW1011**



**KEW1012**

- Display: 6000 counts.
- Bar Graph indication.
- True RMS type. (KEW1012 only)
- Temperature measurement. (KEW1011 only)
- MIN/MAX function.
- Relative measurements.
- Data hold function.
- Automatically turns power off in about 15 minutes to conserve battery life.
- Auto range and manual range selector provided. (with range hold feature)
- Battery voltage warning.
- Designed to international safety standard IEC61010-1 CAT.III 300V / CAT.II 600V.

	KEW1011	KEW1012
<b>DC V</b>	600mV/6V/60V/600V (Input Impedance 10MΩ) ±0.5%rdg±2dgt	
<b>AC V</b>	6V/60V/600V (Input Impedance 10MΩ) ±1.0%rdg±3dgt	
<b>DC A</b>	600μA/6000μA/60mA/600mA/6A/10A ±1.2%rdg±3dgt(600μA/6000μA/60mA/600mA) ±2.0%rdg±5dgt(6A/10A)	
<b>AC A</b>	600μA/6000μA/60mA/600mA/6A/10A ±1.5%rdg±4dgt(600μA/6000μA/60mA/600mA) ±2.2%rdg±5dgt(6A/10A)	
<b>Hz</b>	10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz	
<b>Ω</b>	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ ±1.0%rdg±2dgt(600Ω/6kΩ/60kΩ/600kΩ/6MΩ) ±2.0%rdg±3dgt(60MΩ)	
<b>Diode Test</b>	3V Release Voltage: Approx. 0.4mA Test Current	
<b>Capacitance Test</b>	40nF/400nF/4uF/40uF/400uF/4000uF	
<b>Temperature</b>	-50~+300°C (-58~+572°F)	-
<b>Continuity buzzer</b>	600Ω(Buzzer sounds below 100Ω)	
<b>Withstand Voltage</b>	3700V AC for 1 minute	
<b>Standard</b>	IEC61010-1 CAT.III 300V, IEC61010-031, IEC61326-1	
<b>Power Source</b>	R6P (1.5V) x 2	
<b>Dimensions</b>	161(L) x 82(W) x 50(D) mm	
<b>Weight</b>	280g approx. (Including batteries)	
<b>Accessories</b>	Test Leads, R6P x 2, Instruction Manual, 8216 K type Temperature Probe (KEW1011 only)	



**KYORITSU ELECTRICAL INSTRUMENTS WORKS, LTD.**

No.5-20,Nakane 2-chome, Meguro-ku, Tokyo, 152-0031 Japan

Phone: +81-3-3723-0131 Fax: +81-3-3723-0152

URL: <http://www.kew-ltd.co.jp>

E-mail: [info@kew-ltd.co.jp](mailto:info@kew-ltd.co.jp)

HY07242006