

4-20mA LOOP CALIBRATOR

MODEL 100

- 4-20mA, with 1 μ A resolution
- Basic Accuracy 0.025% + 5 μ A
- Auto-Ramp and Easy Step Functions
- 1-100% Input
- 0-20mA, 0-24mA Selectable
- Easy Just-Type-in Number Operation



PROVA 100

PROVA 100 Specification

Electrical Specification :

Range	Resolution	Accuracy
0-4mA	0.001mA	0.025% + 10 μ A
4-20 A	0.001mA	0.025% + 5 μ A
20-24mA	0.001mA	0.025% + 5 μ A

General Specification:

Battery Type	9V Alkaline Battery (External Power Input 9-15V)
Display	4+5 Digits
Operating Temperature	0 to 50°C (32 to 122°F)
Operating Humidity	Less than 85% relative
Storage Temperature	-20 to 60°C (-4 to 140°F)
Dimension	88 x 168 x 26 mm (3.46" x 6.61" x 1.03")
Weight	330 g / 11.63 oz
Accessories	Carrying case x 1 ; Users Manual x 1 External Battery Pack (without batteries) 9V battery x 1 ; Test leads x 1 ; Alligator clip x 1

TES Electrical Electronic Corp.
 7F, No. 31, Lane 513, Rui Guang Road,
 Neihu Dist. Taipei, Taiwan, R.O.C.
 TEL : 886-2-2799-3660
 FAX : 886-2-2799-5099
 E-mail : tes@ms9.hinet.net