

1339 Light Meter Pro.

MODEL TES-1339

FEATURES :

- Dual Display, 4-digit LCD reading.
- Spectral Sensitivity close to CIE photopic Curve.
- Measuring Levels Ranging 0.01 to 999900 Lux, 0.01 to 99990 fc, Autoranging 5 step.
- Accurate and Instant response.
- Integral illuminance measurement.
- Luminous intensity measurement.
- Data Hold function.
- Data memory and read function.
- Reference value setting for relative or percentage deviation measurement.
- Ripple measurement for STRAY + LIGHT function.
- Time-hold function.
- Point - average function.
- Comparator function.
- Auto power off function.
- CNS 5119 Class□.



Specifications for TES-1339

SPECIFICATIONS :

Display	Dual display 4 digit LCD read out.
Measuring Range	99.99, 999.9, 9999, 99990, 999900 Lux 9.999, 99.99, 999.9, 9999, 99990 fc Auto ranging (5 step) (1 fc = 10.76 Lux)
Overrange Display	OL is displayed
Resolution	0.01 Lux, 0.001 fc
Accuracy	±3% rdg ±5dgt (Calibrated to standard incandescent lamp, 2856°K)
CIE photopic f_v	≤6%
Temperature Characteristics	±0.1%/□
Measuring Rate	Approximately 5 time/sec
Photosensor	Silicon photodiodes
Data Memory Capacity	50 sets. (Direct reading from LCD display)
Operating / Storage Conditions	0□ ~ 50□ <80% RH -10□ ~ 60□ <70%RH
Power Source	6 pcs AAA size Battery
Battery Life (typical)	100 hours
Photosensor Lead Length	150 cm (approx.)
Photosensor Dimensions	100(L) ×60(W) ×27(H)mm
Dimension	150(L) ×72(W) ×33(H)mm
Weight	250g
Accessories	Carrying case, Instruction manual, Battery