

DC/AC CLAMP METER



IEC1010-1 (CAT III 600V)

MODEL TES-3091

- 3-1/2 Digital LCD, 2000 count.
- Pocket size.
- MAX hold / Data hold function.



Specifications for TES-3091

*** AC Current**

Range	Resolution	Accuracy	Frequency Range	Overload protection
200A	0.1A	+/- (2%rdg + 4dgts)	50 / 60Hz	700Arms
700A	1A			

*** AC Voltage**

Range	Resolution	Accuracy	Frequency Range	Input Impedance	Overload protection
600V	1V	+/- (1.5%rdg +4dgts)	50 □ 400Hz	1MΩ	600Vrms


*** Ohms (Resistance)**

Range	Resolution	Accuracy	Overload protection
2KΩ	1Ω	+/- (1%rdg+ 1dgts)	600Vrms

*** Continuity beeper**

Range	Sound Level	Max Open Circuit Voltage	Overload protection
(••))	≤30Ω	3V	600Vrms

GENERAL SPECIFICATIONS

LCD Display :	3-1/2 digits, (MAX 1999). OL for over-range indication.  for Low battery indication.
Power Source :	One 9V battery. (006P or IEC6F22).
Battery Life :	100hr approx.
Operating/Storage: Condition :	0°C to 50°C < 80%RH. -10°C to 60°C < 70%RH.
Dimensions :	188(L) x 62.5(W) x 30.5(H)mm
Weight :	Approx. 185 g
Jaw Opening Diameter :	Cables 27.5 mm
Accessories :	Instruction Manual ,Battery, Test Lead and Carrying Case . [3091/ 3092]

TES Electrical Electronic Corp.